





REV	ECO NO.	DATE	BY	APP'D
A	REL TO PRODUCTION PER ECO 001	1/10/06	KL	



Recommend PCB Layout

Dimensions

Positions	A	B	C
8	7.62	15.56	17.76
10	10.16	18.10	20.30
12	12.70	20.64	22.84
14	15.24	23.18	25.38
16	17.78	25.72	27.92
20	22.86	30.80	33.00
24	27.94	35.88	38.08
26	30.48	38.42	40.62
30	35.56	43.50	45.70
34	40.64	48.58	50.78
40	48.26	56.20	58.40
44	53.34	61.28	63.48
50	60.96	68.90	71.10
60	73.66	81.60	83.80
64	78.74	86.68	88.88

Product Specification




Material

Insulator :Glass-Filled Thermoplastic
UL94V-0 rates, Color-Black
Contact :Brass or Phosphor Bronze
Plated full gold or selected gold in
mating area, 100u" min. tin-lead on
on termination area, with entire contact
under-plated 50u" min. Nickel

Electrical

Contact Resistance :30 milliohms
Max at 1 AMP DC.
Insulation Resistance :1000
magohms at 500 VDC
Dielectric Withstanding Voltage :
500 VAC/rms 60Hz for 1 minute
Current Rating :1 AMP
Volatge Rating :250 VAC/rms 60Hz

R4075 Straight Type



R4076 Right Angle Type

Tolerance	
.x	±0.35
.xx	±0.25

UNIT: mm

CONFIDENTIAL

© Copyright 2006 Regal Electronics, Inc. This drawing is the property of Regal Electronics and contains confidential information, trade secret information and/or know-how which is the property of Regal Electronics. By accepting this drawing, the recipient agrees not to provide, or otherwise make available, the drawing or any information or know-how embodied therein, to any third party without prior written authorization.



DRAWN: KIM	DATE 1/10/06	TITLE: BOX HEADER 2.54mm
CHECKED:	DATE	
ENGINEER:	DATE	
APPROVED:	DATE	
APPROVED:	DATE	
APPROVED:	DATE	
SIZE B	DRAWING NO. R4075/R4076	REV A
SCALE: NONE		SHEET 1 OF 1

NOTE:
This component and all homogeneous subcomponents are RoHS compliant

C-R4075/R4076

A